







PFT CONVEYING PUMPS | 06/2011

PFT ZP 3 XXL

The powerful conveying pump with a conveying capacity of 180 l/min for infinitely adjustable control of the conveying quantity.

Functional description

PFT ZP 3 XXL is the right choice if you require very high conveying capacities. The intermediate mortar pump conveys premixed plasters, mortars or floor screeds mixed by a horizontal mixer, batch or truck mixer, directly to the place of application. The conveying capacity can be infinitely adjusted (version V and FC).

You can turn on/off the PFT ZP 3 XXL as well as infinitely adjust the conveying quantity by a remote control. Thanks to the additional insert of a vibrator with extension hopper a faster filling of the machine by a truck mixer is possible.

Fields of application

For all materials like:

- ► Masonry mortars / light masonry
- Floor screeds (from truck mixer)
- ► Self-levelling compounds
- Spraying concretes
- ... and much more

Advantages at a glance

- big conveying capacity and distance
- conveying quantity infinitely adjust-
- control unit integrated with vibrator control
- can be controlled by a remote control
- with vibrator and extension hopper
- can be filled by a truck mixer
- sealing unit between geared motor and material hopper
- low filling height
- robust construction frame
- > small effort of cleaning and main-
- quick disassembling of pump
- equipped with: cleaning fittings, crane loops





All rights and technical changes reserved. We provide guarantee as far as faultless and proper finishing of our machines is concerned. Figures given in relation to output, equipment and performance are based on experience and can vary in case of changing circumstances. Furthermore, the instructions of the material/mortar manufacturers must be observed. Alterations, reprints and photomechanical reproductions, even in extracts, require the permission of Knauf PFT GmbH & Co. KG.

PFT ZP 3 XXL-GB/1M/06.11/FLY



Knauf PFT

Technical Hotline:

- +49 9323 31-1818
- Phone +49 9323 31-760
- Fax +49 9323 31-770
- ▶ info@pft-iphofen.de
- www.pft.eu

Technical data

PFT ZP 3 XXL FC

Part no.	00 15 11 74	
Conveying capacity*	approx. 7 – 180 l/min	
Conveying distance*	up to 150 m	
Conveying pressure*	max. 20 bar	
Drive	Pump motor:	7.5 kW geared motor
		13 kW power consumption
	Speed:	from 0 – 162 rpm
	infinitely adjustable via fre	
Power connection	Power supply:	400 V, three-phases current
	Fuse protection:	32 Ampere

Dimensions

Hopper content without extension hopper	130 l	
Hopper content with extension hopper	245 l	
Total height	approx.	745 mm (without extension hopper)
Total width	approx.	725 mm
Total length	approx. 3	3,075 mm

Total weight

Depending on mortar quality, components of mortar, consistency of mortar, pump version, condition of pump, diameter of conveying hose and conveying height. Please observe the respective instructions of the material producer.

Basic equipment

Conveying pump PFT ZP 3 XXL with

- Pump unit 2L8 up to 14 mm in grain size
- Geared motor 7.5 kW, 400 V, FC (13 kW power consumption)
- Integrated control unit with frequency converter
- Pressure flange extra long
- Integrated mortar pressure gauge
- Tool ki
- Operating instructions

Accessories

Extension hopper 300 mm with filter inlet and surge box Part no. 00 09 80 04

External vibrator SR6, 400 V Part no. 20708220

Knauf PFT GmbH & Co. KG

P.O. Box 60 97343 Iphofen Einersheimer Straße 53 97346 Iphofen Germany Knaut Gips

Dry construction- and Soil-Systems

Knauf AMF Ceiling Systems

Knauf Bauprodukte Pro Solutions at Home Knauf Gips / Marmorit
Plaster and Facade Systems

approx. 378 kg (without extension hopper)

Knauf Dämmstoffe Polystyrol Insulating Material

Marbos Mortar Systems in Civil Engineering Knauf Insulation Insulating Material: Rock Wool, Glass Wool and Wood Wool

Knauf Integral Gypsum Fibre Technology for Soil, Wall and Ceiling Knauf Perlite AQUAPANEL® Cement Boards, Perlit

Sakret Bausysteme Dry Mortar for New Build and Renovation